



# SmokeCloak *EASY*

SPECIFICATION SHEET





#### Product features

- Very high output of dense white fog for maximum protection
- Harmless dry vapour with no negative side effects
- The fog hangs up to an hour
- Fluid refill system
- Danish design
- Battery back-up
- Heavy duty sabotage resistant case
- Internal system status LED indicators
- Built-in self diagnostics
- Electronic fluid measurement system
- Output signals for communication with existent alarm system
- Input signals for controlling the SmokeCloak from existing alarm system

#### Installation

- Installation, service and maintenance friendly
- Horizontal, vertical and ceiling mounting option
- Seamless integration with all existing alarm systems

#### SmokeCloak EASY

<b>Dimensions</b>	252 mm wide x 193 mm deep x 418 mm high
<b>Installation weight</b>	< 14 kg
<b>Colour</b>	white RAL 9016
<b>Fluid</b>	1,0 litre fluid refill system
<b>Electrical</b>	200 - 250V
<b>Power consumption</b>	1,5KW @ 230V
<b>Reaction time</b>	0,1 seconds
<b>Output</b>	150 m <sup>3</sup> / 30 sec. depending on the application (requirement to the visibility) 250 m <sup>3</sup> / 60 sec. depending on the application (requirement to the visibility)
<b>Pulse Function</b>	Programmable via Dip switch
<b>Heat up time (ready)</b>	9 min.



**TRANSACTION  
CONTROL  
TECHNOLOGIES**

(SA)(Pty) Ltd  
Reg.No. 2001/008728/07

**MORE THAN A SECURITY SOLUTION**

Tel: +27 11 888 1210 • Fax: +27 11 888 1625 • E-mail: solutions@tct.co.za  
Web: www.tct.co.za • PO Box 2723, Northcliff, 2115, South Africa  
An ISO 9001:2008 Company [International patents registered](#)